

tel: +48 (14) 623 02 84; +48 609 605 195;

NIP: 713-287-29-47

tel/fax: +48 (14) 636 06 80;

www.dortech.eu

mail : biuro@dortech.eu

Regon: 121862140

////////////////////////////////////

Instruction how to use the Repair Kit with the rope or the tape

STANDARD REPAIR KIT

The kit contains: **glass rope min. 2,2m** **self-adhesive end tape** **heatproof ceramic glue**

1,2 Tear off the used gasket from the door frame of the fireplace body, remove the remnants of glue with a chisel or screwdriver; clean the groove with a brush and degrease with a cloth moistened with denatured alcohol (if necessary).

3,4 Cut the end tape into two equal parts; remove the paper cover and wrap the end of the gasket without changing the diameter of the rope; cut off any sticking out pieces of the rope together with the end tape - in the same place as the end tape.

5. Spread a thin layer of glue on the bottom of the groove (open the tube by unscrewing the top part of the cap and piercing the tube with the reverse side of the cap); the lower part of the cap (dispenser) can be shortened as needed.

6. Start placing the gasket from the center of the bottom of the groove; place the end of the rope into the groove so that the piece of the end tape is pressed into the glue. Press the gasket into the glue without stretching it while sticking; remove any excess glue with a damp cloth; the sealing side of the rope should not be dirty with glue. After filling the groove with a gasket, adjust its length, adding about 1 cm; secure the other end of the gasket with the remaining piece of the end tape; cut off the excess rope and paste without leaving any gap between the ends of the gasket.

7. Close the door, then open it and check if the gasket fits tightly; leave it to dry for at least 8-10 hours without closing the door.

ATTENTION! Before you light the fireplace, make sure that the glue has set and dried.

8. The glue used in the set has the properties of a cement mortar (slightly alkaline reaction), therefore we suggest the use of personal protective equipment (e.g. latex gloves). In case of possible skin contact, wash the skin. In case of eye contact, rinse the eye thoroughly and see an ophthalmologist. Dispose of the used gasket and the remnants of the adhesive in a municipal waste container.

SELF-ADHESIVE TAPE

The repair kit contains: self-adhesive glass tape (min.2.2 m)

In case of self-adhesive tapes, special care should be taken of the place of gluing.

Instructions for use

Wait until the fireplace has cooled down

- ✓ after sticking the gasket to the door frame, put the glass against the doorframe and tighten the clamps moderately placing short pieces of the gasket under them;
- ✓ check the adhesion of the glass to the seal (with a paper strip), it affects the tightness of the fireplace;
- ✓ dispose of the used gasket in a municipal waste container.



**WE RECOMMEND REPLACEMENT OF THE GASKET ONCE EVERY 2 YEARS
FOR BETTER SAFETY AND LOWER COST OF FIREWOOD**

Production and confection: DORTECH.EU